



FUMIO LUBE

Manufactured by Chautong Trading Co., Ltd.
RM.802, No. 105 Sec. 1 Kai-Feng Street, Taipei 100 Taiwan
Tel : 886-2-2381 8122 Fax : 886-2-231 45 354

LUBRICATING OIL

FL HYDRO 10

FL HYDRO 10 is a range of lubricants with excellent oxidation stability and corrosion protection. Designed for hydraulic and circulating systems.

- FL HYDRO 10 is suitable for all hydraulic applications and circulation systems where an ISO HL/CL typelubricant is recommended.
- The more fluid grades are adapted for system operating at high speed such as textile machines and packaging machines
- The more viscous products are designed for gears and bearings found in wide range of industrial machinery where ant-wear and extreme-pressure properties are not required such as in centrifugal pumps and small turbines
- The products are also suitable where higher working temperature occurs, such as in paper machines
- FL HYDRO 10 is also suitable as compressor oil

PROPERTIES AND ADVANTGES :

- Good oxidation stability ensuring a long product life
- Good demulsification properties allowing a fast water separation
- Good anti-foam characteristics

TYPICAL CHARACTERISTICS :

METHODS	CHARACTERISTICS	ISO GRADES 10
ASTM D 4052	Density at 20°C, kg/l	0.850
ASTM D 445	Viscosity at 40°C, mm ² /s	10.0
ASTM D 445	Viscosity at 100°C, m ² /s	2.6
ASTM D 2270	Viscosity index	110
ASTM D 92	Flash point COC,°C	160
ASTM D 97	Pour point, °C	-20