

FUMIO LUBE

LUBRICATING OIL

Manufactured by Chautong Trading Co., Ltd. RM.802, No. 105 Sec. 1 Kai-Feng Street, Taipei 100 Taiwan Tel : 886-2-2381 8122 Fax : 886-2-231 45 354

FL HYDRO 5

FL HYDRO 5 is range of lubricants with excellent oxidation stability and corrosion protection, designed for hydraulic and circulating systems.

- FL HYDRO 5 is suitable for all hydraulic applications and cirulation systems where an ISO HL/CL type lubricant is recommended.
- The very low viscosity grades are recommended for use in high speed spindles and bearings, e.g. Textile machines and grinding spindles, for hydraulic control applications and for hydrostatic bearing systems.
- The middle viscosity grade are widely used in hydraulic control systems and hydraulic power systems working at moderate pressures and temperatures, they are also suitables foe a wide range of ring oiled or circulation oiled bearings e.g. motor dynamo bearings, textile and packaging machines, small steam turbines, centrifugal pumps, and similar applications.
- The heavier grades are recommended for circulation systems, bearings and gears in machine tools, steam engines, compressors and a wide range of general machinery. They are also particularly useful in mining and quarrying applications e.g. gyratory crushers where easy cold start conditions are required.

PROPERTIES AND ADVANTGES :

- Good oxidation stability ensuring a long product life.
- Good demulsifications properties allowing a fast water separation.
- Good anti-foam characteristics.

Methods	Characteristics	ISO Grades 5
ASTM D4052	Density at 20°C, kg/I	0.836
ASTM D445	Viscosity at 40°C, mm2/s	5
ASTM D445	Viscosity at 100°C, mm2/s	1.5
ASTM D2270	Viscosity index	112
ASTM D92	Flash point COC,°C	132
ASTM D97	Pour point,°C	-20

TYPICAL CHARACTERISTICS :