



FUMIO LUBE

Manufactured by Chautong Trading Co., Ltd.
RM.802, No. 105 Sec. 1 Kai-Feng Street, Taipei 100 Taiwan
Tel : 886-2-2381 8122 Fax : 886-2-231 45 354

LUBRICATING OIL

FL Fumiclean A

Description

A superior quality hydrocarbon system cleaner to use between metalworking processes.

Application

Recommended for washing off neat metalworking fluids (such as cutting oils, forming oils, etc.) and rust preventive oils. It is also suitable for washing processes that requires solvent based cleaner.

Characteristics

1. Excellent performance in washing off unnecessary metalworking fluids from parts
2. User concern cleaner due to its low odor characteristic
3. Does not contain any impurities
4. Safe to use on iron, steel and other non ferrous metal
5. Due to its solvent characteristic, **FL Fumiclean A** has a superior drying ability
6. Recommended for use with parts-washing equipments and ultrasonic cleaning processes

Packing

20L pail, 200L drum

Typical Properties

Appearance		Clear liquid
Specific gravity	20°C	ASTM D4052.....	0.79
Density	15°C	kg/m3.....	777
Color	SAYBOLT – ASTM D156..		+30
Flash Point	°C	ASTM D56.....	44.5
Viscosity	40°C	mm2/s.....	0.943
Water content	wt%	ASTM D1364.....	0.01

The information in this bulletin is, to our best knowledge, true and accurate, but all recommendations or suggestions are without guarantee, since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement