



FUMIO LUBE

Manufactured by Chautong Trading Co., Ltd.
RM.802, No. 105 Sec. 1 Kai-Feng Street, Taipei 100 Taiwan
Tel : 886-2-2381 8122 Fax : 886-2-231 45 354

LUBRICATING OIL

FL FUMICLEAN H 78

HYDROCARBON TYPE CLEANER

FL FUMICLEAN H 78 highly refined, extremely low viscosity, and high purity paraffinic oil. Compared with kerosene that has an equivalent viscosity, this has lower odor, higher flash point, and fewer irritants, and brings out its good ability to clean up oil spots after metalworking or heat-treating.

❖ SPECIAL FEATURES

1. Low viscosity, Low odor, and high flash point.
2. Few irritant.
3. Not be listed in the Ordinance on the Prevention of Organic Solvent Poisoning.
4. Categorized to be 3rd class oil products, 4th group hazardous substance under Fire Defences Law.

❖ TYPICAL PROPERTIES

TEST ITEMS	MEASURE	TYPICAL VALUE	
Density 15°C	g/mm ³	0.790	
Flash Point	°C	79	
Pour point	°C	Under -60	
Color ASTM		Over +30	
Appearance Visual		Clear and colorless	
Viscosity 40°C	mm/s ²	1.64	
Fractional Distillation	I.B.P.	°C	205
	End Point	°C	230
Sulfur Content	%	0.000	

❖ SAFETY

1. Poisonous and Deleterious Substances Control Law : Not applicable
2. Acute Toxicity : LD₃₀ Value (rat – oral): 15 g/kg and over
3. Irritant
Skin : Fewer irritans as compared with those of many other petroleum type solvents

such as gasoline, kerosene.

Eyes : Same as above.