



FUMIO LUBE

Manufactured by Chautong Trading Co., Ltd.
RM.802, No. 105 Sec. 1 Kai-Feng Street, Taipei 100 Taiwan
Tel : 886-2-2381 8122 Fax : 886-2-231 45 354

LUBRICATING OIL

FL WAYLUBE H 220

FL WAYLUBE H 220 is an adhesive and unctuous mineral oil, design for machine tools slide ways and hydraulic lubricate.

❖ APPLICATION

General lubrication of moving components found in industrial equipment such as ring lubrication using drop oil feed where an open system is employed and the lubricant is not recirculated.

Lubrication of vertical and horizontal sideways including passenger lift guides and machine tools camages.

Chains in unsealed system and encased cables.

❖ PROPERTIES

Good adhesion to metal surfaces
Very high lubricity and film strength
Content EP additives can reduce wear on sideways

❖ TYPICAL CHARACTERISTICS

ISO	ASTM test method	220
Gravity at 15	D-1298	0.89
Viscosity 40°C	D-445	220
100		20.4
Viscosity	D-2270	108
Flash point °C	D-92	260
Pour Point °C	D-97	-10

The information in this bulletin is, to our best knowledge, true and accurate, but all recommendations or suggestions are without guarantee, since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement