



FUMIO LUBE

Manufactured by Chautong Trading Co., Ltd.
RM.802, No. 105 Sec. 1 Kai-Feng Street, Taipei 100 Taiwan
Tel : 886-2-2381 8122 Fax : 886-2-231 45 354

LUBRICATING OIL

FL FUMICOOL 672

GENERAL DESCRIPTION

FUMICOOL 672 is a soluble oil or chemical emulsion coolant concentrate. It is effective in general duty machining and grinding of most materials. It provides superior corrosion inhibition, anti-foam and biocide performance.

ADVANTAGES

- Contain high performance lubricant which can increase lubricity & extend tool life.
- Machines & parts are easily washed off with coolant working solution
- Good antifoam & microbial control performance
- Superior corrosion inhibition for protecting alloy surface

TYPICAL CHARACTERISTICS

Form.....	Liquid
Color.....	Yellow/Orange
Density (g/cm ³ ;15 °C).....	1.00
Typical Emulsified Mixture Color (20x).....	Light Yellow
Flash Point.....	None to Boiling (COC)
pH Typical Operating Range.....	9.5

The information in this bulletin is, to our best knowledge, true and accurate, but all recommendations or suggestions are without guarantee, since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement