

FUMIO LUBE

Manufactured by Chautong Trading Co., Ltd. RM.802, No. 105 Sec. 1 Kai-Feng Street, Taipei 100 Taiwan Tel: 886-2-2381 8122 Fax: 886-2-231 45 354

LUBRICATING OIL

FL FUMICOOL SB - 25

FL FUMICOOL SB-25 is emulsion type low septic EP cutting and grinding fluid for general use.

SPECIAL FEATURES *

- 1. Used for general cutting/grinding works of steel, featured to extend service life of tools and to improve smoothness of finished surface.
- Excellently protect steel and non-ferrous metals from rust and corrosion. 2.
- Used good anti-septic agent to suppress fluid deterioration, make it possible to use the fluid/solution for a longer period.
- 4. Good cleaning ability and de-foaming characteristics provide good workability.

TYPICAL USES AND STANDARD DILUTING RATIOS

Material to work: General cutting / grinding work of steel (including stainless steel) and aluminum. Detailed works:

1.	Cutting works of steel (incl. stainless steel)		
	by NC lathe, boring, milling and transfer machine	5 % ~ 10 %	
2.	Cutting works of aluminum alloys by	3 % ~ 10 %	
3.	NC Lathe, boring, milling and transfer machine	5 % ~ 20 %	
4.	Threading, Tapping and reaming	3 % ~ 5 %	
5.	Grinding works of steel (incl. stainless steel and aluminum alloys)	3 % ~ 5 %	
6.	Sawing works of steel and non –ferrous metals by machine saw	3 % ~ 5 %	

TYPICAL PROPERTIES * (Tested with diluted solution of 10%)

Density (15	%)g/cm ³	0.951	
Appearance, Raw Flui	d	Reddish brown fluid	
Appearance, Diluted S	Solution (*)	Milky white emulsion	
PH (*)		9.35	
Surface Tension (*) dy	yne/cm	34.0	
Rust Preventing	2.5 % diluted solution	Chip method/ No Change	
Performance FC-20	5 % times diluted solution	Match method/ No Change	
24 hr			
Influence on non-ferro	ous metals (*)	Steel (C-1100P)/ No discolor	
Room Temperature x	48 hr	Aluminum (A-1050p)/ No discolor	
Emulsion Stability (*)	ml/100ml, Room temp x 24 hr	Oil cream/ Trace	