WASHING AGENTS :

BEFORE



AFTER

CLEAN SUPER

WASHING AGENTS : CLEAN SUPER

LIKAN'S CLEAN SUPER PRODUCTS ARE METAL CLEANING PRODUCTS TO BE USED WIDELY IN VARIOUS INDUSTRIAL PLANTS, SUCH AS ELECTRONIC COMPONENTS, AUTOMOTIVE PARTS AND CAN ALSO BE USED AS CLEANING SUBSTANCE CFC - FREE RESIDUAL POLLUTION IN THE ENVIRONMENTAL. THEY ARE ALSO CAPABLE OF CLEANING SOLUTION SIMILAR TO WASHING AGENT SOLVENT TYPE.

FEATURES

- USED FOR CLEANING AND REMOVING OIL SUCH AS CUTTING OIL, SHAVING OIL AND RESIN.
- USED AS A CLEANING AGENT IN HEAT-TREATMENT PROCESS.
- USED FOR CLEANING ALL KIND OF METAL.
- ANTI-CORROSION.
- WASTE WATER TREATMENT EASIER.

WASHING AGENTS: CLEAN SUPER

LIKAN *CLEAN SUPER* ADALAH PRODUK PEMBERSIH LOGAM YANG BANYAK DIGUNAKAN DALAM BERBAGAI INDUSTRI, SEPERTI KOMPONEN ELEKTRONIK, SUKU CADANG OTOMOTIF DAN JUGA DAPAT DIGUNAKAN SEBAGAI PEMBERSIH SISA POLUTAN BEBAS CFC PADA LINGKUNGAN. PRODUK INI MAMPU MEMBERSIHKAN LAYAKNYA CAIRAN PEMBERSIH TIPE SOLVENT.

FITUR

- UNTUK MEMBERSIHKAN MINYAK, SEPERTI *CUTTING OIL, SHAVING OIL* DAN RESIN
- SEBAGAI ALAT PEMBERSIH PADA PROSES PERLAKUAN PANAS / *HEAT TREATMENT*
- MEMBERSIHKAN SEMUA BAHAN LOGAM
- ANTI KOROSI
- MEMPERMUDAH PENGOLAHAN AIR LIMBAH

BEFORE

AFTER

WASHING AGENTS : CLEAN SUPER

PRODUCT	PH (1% SOL)	APPLICATION	USAGE	APPEARANCE/PACKAGE
CLEAN SUPER 2025	10.2 ± 0.5	WASHING AGENT FOR STEEL, STAINLESS REMOVE HIGH VISCOSITY OIL	3 - 10 % SOL./ 40 - 70°C DIPPING	LIGHT YELLOW CLEAR LIQUID 20 KGS. / PAIL
CLEAN SUPER 285	9.5 ± 0.5	WASHING AGENT FOR ALL METAL WASHING BEFORE PAINTING PROCESS	3 - 5 % SOL./ 60 - 70°C DIPPING, SPRAY	LIGHT YELLOW LIQUID 20 KGS. / PAIL
CLEAN SUPER 285 J	9.9 ± 0.5	WASHING AGENT FOR STEEL LOW FOAMING TYPE	3 - 5 % SOL. ROOM TEMP - 80°C DIPPING	LIGHT YELLOW LIQUID 20 KGS. / PAIL
CLEAN SUPER 285 K	10.0 ± 0.5	WASHING AGENT FOR STEEL OR FROM HEAT TREATMENT PROCESS	3 - 5 % SOL./ 60 - 70°C DIPPING, SPRAY	LIGHT YELLOW LIQUID 20 KGS. / PAIL
CLEAN SUPER 285 N	9.9 ± 0.5	WASHING AGENT FOR ALUMINIUM	3 - 5 % SOL./ 60 - 70°C DIPPING, SPRAY	LIGHT YELLOW LIQUID 20 KGS. / PAIL
CLEAN SUPER 288	8.7 ± 0.5	WASHING AGENT IN HEAT TREATMENT PROCESS (FOR SEMI - HOT AND HOT OIL)	3 - 5 % SOL./ 60 - 70°C DIPPING, SPRAY	LIGHT YELLOW CLEAR LIQUID 20 KGS. / PAIL
CLEAN SUPER 866	9.4 ± 0.5	WASHING AGENT IN HEAT TREATMENT PROCESS (FOR COLD OIL)	3 - 5 % SOL./ 60 - 70°C DIPPING, SPRAY	WHITE MILKY LIQUID 20 KGS. / PAIL
CLEAN SUPER 90	9.0 ± 0.5	EMULSION TYPE WASHING AGENT IN HEAT TREATMENT PROCESS (FOR SEMI - HOT AND HOT OIL)	3 - 5 % SOL./ 60 - 70°C DIPPING, SPRAY	LIGHT YELLOW CLEAR LIQUID 20 L. / PAIL
CLEAN SUPER 98	9.0 ± 0.5	EMULSION TYPE WASHING AGENT IN HEAT TREATMENT PROCESS (FOR SEMI - HOT AND HOT OIL) LOW FOAMING TYPE, REMOVE HIGH VISCOSTITY OIL	3 - 10 % SOL./ ROOM TEMP - 70°C DIPPING, SPRAY	LIGHT YELLOW CLEAR LIQUID 20 L. / PAIL
CLEAN SUPER M-510	9.7 ± 0.5	WASHING AGENT AFTER HEAT TREATMENT PROCESS (FOR REMOVE ANTI-CARBON)	3 - 5 % SOL./ 60 - 70°C DIPPING, SPRAY	LIGHT YELLOW CLEAR LIQUID 20 KGS. / PAIL
CLEAN SUPER 5040	11.7 ± 0.5	WASHING AGENT FOR STEEL, STAINLESS REMOVE HIGH VISCOSITY OIL	3 - 5 % SOL./ 60 - 70°C DIPPING, SPRAY	LIGHT YELLOW CLEAR LIQUID 20 KGS. / PAIL
CLEAN SUPER 5050	11.8 ± 0.5	WASHING AGENT FOR PLASTIC BOX	3 - 5 % SOL./ 60 - 70°C DIPPING, SPRAY	LIGHT YELLOW CLEAR LIQUID 20 KGS. / PAIL
CLEAN SUPER 516 M	10.5 ± 0.5	WASHING AGENT FOR ALUMINIUM AND BEFORE PAINTING PROCESS	3 - 5 % SOL./ 60 - 70°C DIPPING, SPRAY	NON COLOUR CLEAR LIQUID 20 KGS. / PAIL
CLEAN SUPER E 210 MB	10.1 ± 0.5	WASHING AGENT FOR STEEL, ALUMINIUM AND COPPER	3 - 5 % SOL./ 40 - 70°C DIPPING, SPRAY	YELLOW LIQUID 20 KGS. / PAIL
CLEAN SUPER E 210 P	9.8 ± 0.5	WASHING OIL FOR STEEL, PASTIC BOX	3-5 % SOL. ROOM TEMP - 80°C	YELLOW LIQUID 20 KGS. / PAIL
CLEAN SUPER KL-12	2.5 ± 0.5	WASHING AGENT FOR COPPER, ALUNINIUM AND STAINLESS REMOVE OIL AND RUST	5 - 50 % SOL. ROOM TEMP - 70°C DIPPING	LIGHT YELLOW CLEAR LIQUID 20 KGS. / PAIL
CLEAN SUPER L 208 N KAI 2	12.3 ± 0.5	WASHING AGENT FOR MOULD CLEANING REMOVE PLASTIC GAS, ALUMINIUM, RUBBER	5 - 100 % SOL.ROOM TEMP - 70°C DIPPING, ULTRASONIC	SEMITRANSPARENT LIQUID 20 KGS. / PAIL
CLEAN SUPER M-38	11.5 ± 0.5	WASHING AGENT FOR STEEL, PLASTIC BOX	3 - 5 % SOL./ 60 - 70°C DIPPING, SPRAY	LIGHT YELLOW CLEAR LIQUID 20 KGS. / PAIL
CLEAN SUPER M-801	10.3 ± 0.5	WASHING AGENT FOR STEEL, ALUMINIUM	3 - 5 % SOL./ 60 - 70°C DIPPING, SPRAY	LIGHT YELLOW LIQUID 20 KGS. / PAIL
CLEAN SUPER NAL 30	7.5 ± 0.5	WASHING AGENT FOR ALL METAL NEUTRAL TYPE	3 - 5 % SOL./ 60 - 70°C DIPPING, SPRAY	LIGHT YELLOW CLEAR LIQUID 20 KGS. / PAIL
CLEAN SUPER SL	11.2 ± 0.5	WASHING/POLISHING AGENT FOR STEEL	3 - 5 % SOL./ 60 - 70°C DIPPING, SPRAY	LIGHT YELLOW POWDER 20 KGS. / CASE
CLEAN SUPER SR	10.7 ± 0.5	WASHING AGENT FOR ALUMINIUM, ZINC	3 - 5 % SOL./ 60 - 70°C DIPPING, SPRAY	NON COLOUR CLEAR LIQUID 20 KGS. / PAIL
CLEAN SUPER TL	12.5 ± 0.5	WASHING AGENT FOR STEEL AND FOR WASHING BEFORE PLATING PROCESS	3 - 5 % SOL./ 60 - 70°C DIPPING	LIGHT YELLOW POWDER 20 KGS. / CASE
PEARL CLEAN 200 A	-	WASHING AGENT SOLVENT TYPE	DIPPING ROOM TEMP.	COLORLESS AND CLEAR LIQUID 200 L. / DRUM
PEARL CLEAN BT-92	-	WASHING AGENT FOR ALUMINIUM, STAINLESS (PAINT REMOVE)	100 % SOL./ 80°C DIPPING	COLORLESS AND CLEAR LIQUID 20 KGS. / PAIL
PEARL CLEAN D-40D	-	WASHING AGENT SOLVENT TYPE RAPID DRY TYPE	DIPPING ROOM TEMP.	COLORLESS AND CLEAR LIQUID 200 L. / DRUM
SCC-24	3.7 ± 0.5	WASHING AGENT FOR COPPER, BRASS AND STAINLESS MILD ACID TYPE	FOR BARREL	COLORLESS AND CLEAR LIQUID 20 KGS. / PAIL
YANICLEAN N-5	9.5 ± 0.5	WASHING AGENT FOR CLEANING WAX AND RASIN	5 - 10% SOL./ 60 - 70°C DIPPING, SPRAY	NON COLOUR CLEAR LIQUID 20 KGS. / PAIL