TOOL SET UP STATION

Tool washing CLEAN BOX

• Wash tool holders, cutting tools and jig fixtures.

- No plumbing required.
- Safe cleaning system using water.
- Built-in water heater improves washing capability.





CODE

CBX-01

Compact built-in sink





Automatic washing space


Shoots cleaning fluid from 18 location nozzles.



Hand washing

Heavy dirt can be Built-in sink with washed off using an overflow drain the hand nozzle (40°C/104°F)







Top cover

Top cover of washing unit can be opened and closed with one hand.

Comes with an automatic shutoff function for the washing cycle.

Automatic washing stops automatically when the top cover is lifted during operation.



Washing Unit

18 nozzles shoot hot water from every angle to wash off all the dirt.




Timer operating mode

Operation can be stopped automatically using the clock timer. (The time can be set arbitrarily, up to 12 min.)



Light dirt can be washed off using automatic washing.

Heavy dirt can be washed off by hand.





Filter

Can be changed easily when it becomes dirty.

Outer sink cover

Hand nozzle

Easy to attach and detach.

Prevents splashing of the

washing cleaner.



Attach



Remove

Main filter

Sub-filter

Tank

The use of heated cleaning fluid (40°C) increases the cleaning power and makes cleaning easy even in the winter.







Be sure to use watersoluble cleaning fluid.

The sink, washing unit and tank are made of stainless steel, resulting in easy maintenance and less staining.

Dimensions





Specification

Material	SU304 (Sink, Tank, Cleaning unit) SS 400 (Base frame)
Tank	Approx. 65L (Level gauge with thermometer is standard accessory.)
Pump	0.3~0.51kW (50/60Hz) (Produced by Grundfos)
Heater	3kW (with temperature control)
Weight	Approx. 100kg (165kg, including cleaning fluid)
Voltage	3-phase 200V (Rated 15A)

Std. Access.

CODE	Description	Q'ty
CBX-HNZ	Hand nozzle	1pc.
-MFIL	Main filter	2pcs.
-SFIL	Sub-filter	2pcs.
-TRP	Drain trap	1pc.
-GSTP	Rubber drain plug	1pc.
-WBSK	Washing basket	1pc.
-WTBL	Washing table	1pc.
Sink outer cover		1set
Hook		2pcs.
Bamboo brush		1pc.
Primary power code (plug attached 15m)		1pc.

■Caution


- •Be sure to use water-soluble cleaning fluid.
- Customers pay the shipping cost.
- •200V electric power supply (transformer is required)

Option

Draining basket

Uniformity with stand load 40kg CODE ■Std. Access. CBX-SBX





Used for draining, air blowing, rust-proofing, etc. Can be attached to either the right or left side of the unit.

Main filter

CODE Q'ty

CBX-MFIL 5pcs.

Hand nozzle

CODE

Consumables / Replacement parts

Washing basket

CODE	
CBX-WBSK	

Collet and small parts can be





Washing table CODE

CBX-WTBL

Used in a sink as an auxiliary











Sub-filter

CODE Q'ty

CBX-SFIL 3pcs.







