



Toyosaki Bldg., 18-21 Chayamachi Kita-ku Osaka∓530 TEL(06)373-0171 FAX(06)373-0174

RUSFIGHTER 315

RUSFIGHTER 315 is a solvent diluent's type, mineral oil based anti-rust oil, corresponding to JIS K 2246 Class 3 (NP-3-1). This oil forms a very thin film after solvent evaporation.

*** SPECIAL FEATURES**

- 1. Has good cleaning, water replacement and demulsifier properties.
- 2. Though formed film is thin, it has awesome anti-rust properties. (against humidity and salt water).
- 3. Has an excellent protective property against oil stains.
- 4. Dries quickly and makes no sticky oil film.
- 5. Has easy workability and handle ability.

APPLICATION: Used for;

- 1. De-watering and rust proofing materials rinsed in water after chemicals/ acids treating or shot blasting/ preening.
- 2. De-watering and rust proofing materials machined with water-soluble cutting/ grinding fluids.
- 3. De-watering and rust proofing materials machined with water-soluble quenching fluids.
- 4. Rust proofing general materials for a short term for machining operations or medium range rust proofing.

* APPLICATION METHOD

Can be used for methods such as dipping, spray, brushing, showering, at room temperature.

* REMOVING METHOD

Films are removable with lye, petroleum or other solvents (by dipping, wiping, and vaporing).

***** TYPICAL PROPERTIES

TEST ITEMS	TEST CONDITIONS	MEASURE	TYPICAL VALUE
Appearance			Liver clear fluid
Color (ASTM)			L3.5
Viscosity	40 °C	mm²/s	1.31
Flash point (PM)		°C	45.0
Copper Corrosion	50 °C 3hr		1a
Humidity Cabinet		Class	720h-A
Salt Spray		Class	48h-A
Demulsibility	Oil-Water Emulsifying ml	minute	40-40-0