



RUSFIGHTER 60 – 1

Petrolatum Type

RUSFIGHTER 60 – 1 is an anti-rust petrolatum, corresponding to Petrolatum Type Rust Preventive Oil Class 1 stipulated by JIS K 2246 (NP-6). This oil forms petrolatum films.

◇ **SPECIAL FEATURES**

1. Possible to change the thickness of film flexibly by heating temperature control.
2. Superior to Solvent Dilution Type in the point of risk of fire.
3. Has strong anti-rust property, so suitable for export ~ long-term rust proofing.
4. Also suitable for anti-corrosion of nonferrous metal.

◇ **APPLICATION**

1. long-term rustproofing for products with precision finish, such as bearings, cylinders, pistons, spindles, gears, and valves.
2. Rustproofing and lubricating machinery's sliding or other each parts.
3. Long-term rustproofing for general materials such as chains, and bolts.

◇ **APPLICATION METHOD**

Dip coating by heating (70 °C - 100 °C) or brushing at room temperature.

* Please avoid to heat products in high-temperature and long-term.

◇ **REMOVING METHOD**

- Wipe it out by rags solvent infiltrated.
- Expose it to high-temperature atmosphere (over melting point of this product — dryer), or soak it in solvent.

◇ **TYPICAL PROPERTIES**

TEST ITEMS		TYPICAL VALUE
Appearance		Claybank, paste form
Penetration (Petrolatum Method)	25°C	230
Melting point	°C	65
Flash point (COC)	°C	230
Humidity Cabinet	hr	2160-A
Salt Spray	hr	240-A
Indoors storage		1 year and over