



NIPPON GREASE CO., LTD.

Toyosaki Bldg.,
18-21 Chayamachi Kita-ku Osaka 〒530
TEL(06)373-0171 FAX(06)373-0174

RUSFIGHTER BS - DRY

RUSFIGHTER BS-DRY forms a semihard wax film after solvent evaporation, suitable for a long-term rustproofing.

SPECIAL FEATURES

1. Having elasticity, the film excels in resistance against cold, bending, impact and check.
2. Compared with asphalt type or varnish type, the film is easier to be removed.
3. Suitable for indoor long term/ final rustproofing.

APPLICATIONS

Rustproofing for :

- ◆ Automobile under coat, underbody, propeller shaft and chassis.
- ◆ Spare parts of marine engine (such as crank shaft, piston)
- ◆ Metallic mold, chain, spring, roll and gear.

HOW TO APPLY

At room temperature, every method is applicable, such as dipping, spraying, brushing and showering.

HOW TO REMOVE

Petroleum aliphatic solvent or various solvents can remove the film by dipping or vaporizing.

TYPICAL PROPERTIES

Test Items	Typical Values
Appearance	Dark Brown, Liquid
Viscosity (40 °C) mm ² /s	63.67
Flash Point °C	50.0
Humidity cabinet test hr	1440-A
Salt spray test hr	240-A
Drying Property (24h)	Pass
Film Thickness μ m	26.4
Film Color	Dark Brown
Indoors storage test	Over 1 year

000806/001MS

- Please read handling instructions on the container carefully when you use this product.
- Described properties and performances do not necessarily guarantee accuracy and perfectness. These are subject to change without notice.

CATL-E-430690