



NIPPON GREASE CO.,LTD.

Toyosaki Bldg.,
18-21 Chayamachi Kita-ku Osaka 〒530
TEL(06)373-0171 FAX(06)373-0174

RUSFIGHTER METAL 4

Rusfighter Metal 4 meets JIS anti – rust oil NP-3 specifications solvent diluted low viscosity mineral oil type anti-rust oil. It will left thin oil film after solvent evaporated. This thin film can prevent metal stuff melt in welding operation.

SPECIAL FEATURES

1. Low viscosity can protect big areas, makes it very economic.
2. Idea middle anti-rust oil during metalworking.
3. Easy be remove by solvent or alkaline solution.
4. Can prevent metal stuff melt in welding operation.

TYPICAL PROPERTIES

Viscosity	cst at 40 °C	1.85
Flash point	°C	45
Wet room anti-rust test (Copper) hr		720A
In-house storage		3 months
color		Brown

APPLICATIONS

1. Good for metal wire, spring and chain anti-rust use.
2. General machine one step short-term anti-rust process oil.
3. Idea anti-rust oil for electric welding operation.

APPLY METHODS

By spray, dipping, immersion, by brush at room temperature.

REMOVAL

By solvent, alkaline solution (immersion, hot bath).