



RUSTFIGHTER 90 – 3

Rustfighter 90-3 meets JIS anti-rust oil NP-9 specifications low viscosity type oil. It made by high refined low viscosity high flash point base oil mixed with anti-rust additive, anti-oxidation additive, pour point depression additive become a very light viscosity anti-rust and lubricating oil.

SPECIAL FEATURES

1. very good low temperature fluidity.
2. low viscosity can protect big areas, makes it very economic.
3. content water replacement characteristic.

TYPICAL PROPERTIES

Test Items	Typical Values
Viscosity cst at 40°C	8.1
Flash point °C	150
Pour point °C	- 30
Wet room anti-rust test (Copper) hr	1080A ⁺
In-house storage	6 months
Color	Brown

APPLICATIONS

1. Low temperature or room temperature use for machine moving parts lubrication and anti-rust use.
2. General machine one step short-term anti-rust process oil.
3. Can use at precession parts, bolts, etc.

APPLY METHODS

By spray, dipping, immersion, by brush at room temperature.

REMOVAL

By solvent, alkaline solution (immersion, hot bath).



NIPPON GREASE CO.,LTD.

Toyosaki Bldg.,
18-21 Chayamachi Kita-ku Osaka 〒530
TEL(06)373-0171 FAX(06)373-0174