NIPPON GREASE CO., LTD. Toyosaki Bldg., 18-21 Chayamachi Kita-ku Osaka = 530 TEL(06)373-0171 FAX(06)373-0174

NIGACE U

NIGACE U is multi purpose long life grease, which base oil is refined mineral oil and thickener is urea. **NIGACE U** compounds stringently selected additives such as an antirust.

✤ APPLICATIONS : Lubrications for ;

Construction machines/ Automotives and motor vehicle electrical components/ Various types of mechanical handling equipment s (convey), working machinery and industrial machinery.

✤ <u>SPECIAL FEATURES</u>

- 1. Usable at high operating temperature.
- 2. Good water resistance.
- 3. Excellent shear stability provides fewer leaks of grease and long life running.
- 4. Usable for points applied heavy load.

PACKAGES

180 kg / Drum 16 kg / Pail

TYPICAL PROPERTIES

TEST ITEMS			NO. 1	NO. 2	TEST METHOD
Appearance			Tan Colo	r-Butyroid	-
Penetration	(25°C)		320	280	JIS K 2220 5.3
Dropping Point		°C	265	265	JIS K 2220 5.4
Copper Corrosion	(100°C 24 h)		1 a	1 a	JIS K 2220 5.5
Evaporation Loss	(99°C 22 h)	mass %	0.40	0.40	JIS K 2220 5.6
Oil Separation	(100°C24 h)	mass %	2.0	1.3	JIS K 2220 5.7
Oxidation Stability	(99°C 100 h)	Mpa	0.025	0.025	JIS K 2220 5.8
Worked Stability	(10^5 time)		360	320	JIS K 2220 5.11
Water Washout	(79°C 1hr)	mass %	3.0	1.0	JIS K 2220 5.12
Timken OK Load	Kg(lb) 10 mi	n	12.2	12.2	JIS K 2220 5.16