



NIPPON GREASE CO., LTD.

Toyosaki Bldg.,
18-21 Chayamachi Kita-ku Osaka 〒530
TEL(06)373-0171 FAX(06)373-0174

NIGLUBE MP-DX NO. 2

NIGLUBE MP-DX is a yellow brown colored multipurpose grease with lithium thickener. **NIGLUBE MP-DX** is not only excellent in resistance to water as a normal lithium based grease, but also preferable for use under extreme operating conditions such as high temperature and heavy load.

USES :

NIGLUBE MP-DX is recommended for use on wheel bearings, gear boxes, cranes, hydraulic generators, cement plant, press rollers, etc., particularly on such places where water may come in contact. The grease can be used for a considerably long period without losing its stability and load resisting effects.

Grade No.1 is suitable for use on central dispensing system, and grades No. 2 and No. 3 are for application by hands and/or grease guns.

TYPICAL PROPERTIES

| Grade : | No. 2 |
|--|--------------|
| Penetration at 25C | 278 |
| Dropping point °C | 199 |
| Evaporation loss 99°C 22hrs wt% | 0.38 |
| Worked stability 100,000W | 296 |
| Oxidation stability 99°C 100hrs kg/cm ² | 0.25 |
| Copper strip corrosion 100°C 24hrs | 1a |
| Oil separation 100°C 24hrs wt % | 0.6 |
| Water resistance 79°C 1hrs wt % | 4.9 |