



**NIPPON GREASE CO.,LTD.**

Toyosaki Bldg.,  
18-21 Chayamachi Kita-ku Osaka 〒530  
TEL(06)373-0171 FAX(06)373-0174

## MNS # 2 GREASE

### Introduce Product

- MNS No. 2 Grease is cooperation development MITSUBISHI Electronics Co.,Ltd and Nippon Grease.
- This Grease developed for big transfer switch and Electric conductive point lubrication
- This special grease good heat endure, good water endure and good oxidation stability, their fore product content mainly Silicon oil, inorganic penetration and graphite, other additive.

### Special Features

- Usable wide range operating temperature (-40~+ 200 °C)
- Good heat stability usable long time.
- Good water resistance.
- Good oxidation stability.

### Applications : Lubrications for ;

- Knife Switch edge
- Contractor face. Slide resistance.
- Other electric conductive point, electric parts high temperature point lubricant.

### Typical Properties

Test Items	Typical Value	Test Method
Penetration (Worked, 25 °C)	236	JIS K 2220 7
Dropping Point °C	>250	JIS K 2220 8
Copper Corrosion (B method 100 °C, 24 H)	OK	JIS K 2220 9
Evaporation Loss (99 °C, 22 H) mass %	0,2	JIS K 2220 3
Ash Content ( A method,) mass %	19,5	JIS K 2220 14
Water Content mass %	0	JIS K 2220 22